NSN 5950-00-102-5930

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-102-5930

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.120 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.120 inches single mounting facility single center group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to single phase single component |
| Body Length: |
| 3.860 inches |
| Body Width: |
| 2.620 inches |
| Body Height: |
| 1.690 inches |
| Maximum Operating Temp: |
| 100.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 7 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 40.0 milliamperes ac single component 4th secondary |
| Winding Operating Voltage: |
| 9.00 ac volts single component 1st secondary |
| Special Features: |
| 1primary winding; 7secondary windings |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 22 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-102-5930

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0