NSN 5950-00-104-1293

Radio Frequency Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-104-1293

Reliability Indicator:
Not established
Inductance Rating:
2.20 microhenries single component single winding
Coil Form Type:
Solid single component
Core Construction:
Powdered single component
Body Length:
0.375 inches
Overall Diameter:
0.157 inches
Maximum Operating Temp:
125.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component single winding
Features Provided:
Tinned wire leads
Tinned wire leads Winding Operating Current:
Winding Operating Current:
Winding Operating Current: 980.0 milliamperes dc single component single winding
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control Shelf Life:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control Shelf Life: N/a
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control Shelf Life: N/a
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control Shelf Life: N/a Unit Of Measure:
Winding Operating Current: 980.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 0.150 single component single winding Quality Factor: 50 single component single winding Terminal Type And Quantity: 2 wire lead Specification Data: 36180-b96-17787 manufacturers specification control Shelf Life: N/a Unit Of Measure: Demilitarization: