

View Online at <https://aerobasegroup.com/nsn/5950-00-105-3356>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

External inclosure single component

**Body Length:**

Between 1.781 inches and 1.844 inches

**Body Width:**

Between 0.969 inches and 1.031 inches

**Body Height:**

Between 1.594 inches and 1.656 inches

**Distance Between Mounting Facility Centers:**

1.250 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Qty Per Inch (tpi):**

40 single group

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

5.3 milliamperes dc single component single primary

**Winding Operating Voltage:**

4.74 ac volts single component single secondary and 9.48 ac volts single component single secondary and 31.74 ac volts single component single secondary

**Test Data Document:**

10001-2616613 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0