

View Online at <https://aerobasegroup.com/nsn/5950-00-105-3356>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

Between 1.781 inches and 1.844 inches

Body Width:

Between 0.969 inches and 1.031 inches

Body Height:

Between 1.594 inches and 1.656 inches

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

5.3 milliamperes dc single component single primary

Winding Operating Voltage:

4.74 ac volts single component single secondary and 9.48 ac volts single component single secondary and 31.74 ac volts single component single secondary

Test Data Document:

10001-2616613 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0