

View Online at <https://aerobasegroup.com/nsn/5950-00-105-5505>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.937 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.062 inches

Body Width:

1.312 inches

Body Height:

1.750 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

320.0 milliamperes ac single component single secondary

Winding Operating Voltage:

37.00 ac volts single component single secondary or 39.00 ac volts single component single secondary

Test Data Document:

13499-672-0323-010 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0