

View Online at <https://aerobasegroup.com/nsn/5950-00-106-5276>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.180 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.765 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

2.875 inches

Body Width:

2.500 inches

Body Height:

2.130 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Voltage:

3.15 ac volts single component 1st secondary and 4.50 ac volts single component 1st secondary and 5.00 ac volts single component 1st secondary and 6.35 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0