

View Online at <https://aerobasegroup.com/nsn/5950-00-106-8465>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and corrosion resistant and salt spray resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded to inclosure single component

Body Length:

Between 2.434 inches and 2.440 inches

Body Width:

Between 1.804 inches and 1.810 inches

Body Height:

Between 1.934 inches and 1.940 inches

Maximum Operating Temp:

136.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

0.61 amperes ac single component 1st secondary

Winding Operating Voltage:

52.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0