

View Online at <https://aerobasegroup.com/nsn/5950-00-106-8465>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant and corrosion resistant and salt spray resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.250 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Core grounded to inclosure single component

**Body Length:**

Between 2.434 inches and 2.440 inches

**Body Width:**

Between 1.804 inches and 1.810 inches

**Body Height:**

Between 1.934 inches and 1.940 inches

**Maximum Operating Temp:**

136.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

0.61 amperes ac single component 1st secondary

**Winding Operating Voltage:**

52.00 ac volts single component all secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0