

View Online at <https://aerobasegroup.com/nsn/5950-00-109-0688>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.625 inches

Body Width:

3.938 inches

Body Height:

4.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

20.8 amperes ac single component single secondary and 35.7 amperes ac single component single secondary

Winding Power Rating:

250.0 volts-amperes single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0