

View Online at <https://aerobasegroup.com/nsn/5950-00-110-0915>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 6.300 inches and 6.500 inches

Body Width:

Between 5.250 inches and 5.380 inches

Body Height:

Between 2.880 inches and 3.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes ac single component single secondary and 9.0 amperes ac single component single secondary

Winding Operating Voltage:

18.20 ac volts single component single secondary and 48.20 ac volts single component single secondary and 48.20 ac volts single component single secondary and 64.30 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

30 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0