

View Online at <https://aerobasegroup.com/nsn/5950-00-110-3302>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.188 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.188 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

11.0 decibels single component

**Body Length:**

4.000 inches

**Body Width:**

3.000 inches

**Body Height:**

3.250 inches

**Maximum Operating Temp:**

200.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 6 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

6.30 ac volts single component 2nd secondary

**Special Features:**

2primary windings; 6 secondary windings

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

20 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0