NSN 5950-00-113-1296

Power Transformer - Page 1 of 2



view Online at https://aerobasegroup.com/nsr//3930-00-113-1296
Reliability Indicator:
Not established
Overall Length:
6.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.562 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.625 inches single mounting facility single center group
Mounting Hole Diameter:
0.250 inches single group
Frequency Rating:
47.0 hertz single component and 63.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
4.750 inches
Body Width:
4.500 inches
Maximum Operating Temp:
105.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
32.0 amperes ac single component single secondary
Winding Operating Voltage:
115.00 ac volts single component single primary
Test Data Document:
24930-63578 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
5 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-00-113-1296

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0