

View Online at <https://aerobasegroup.com/nsn/5950-00-113-1296>

Reliability Indicator:

Not established

Overall Length:

6.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.562 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.750 inches

Body Width:

4.500 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

32.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Test Data Document:

24930-63578 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0