

View Online at <https://aerobasegroup.com/nsn/5950-00-113-5162>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.562 inches

Body Width:

2.875 inches

Body Height:

3.031 inches

Maximum Operating Temp:

55.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

120.00 ac volts single component single primary and 208.00 ac volts single component single primary and 220.00 ac volts single component single primary and 440.00 ac volts single component single primary

Terminal Type And Quantity:

4 pin and 4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0