

View Online at <https://aerobasegroup.com/nsn/5950-00-113-8266>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.437 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.120 inches single mounting facility single center group

Mounting Hole Diameter:

0.200 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.120 inches

Body Width:

2.870 inches

Body Height:

3.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

3.0 amperes ac single component single primary

Winding Operating Voltage:

76.00 ac volts single component 2nd secondary

Test Data Document:

56000-67116 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0