## NSN 5950-00-114-1510

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-114-1510

| Reliability Indicator:  |
|---|
| Not established   |
| Overall Length:   |
| 2.812 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 1.188 inches single mounting facility single center group   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.188 inches single mounting facility single center group   |
| Frequency Rating:   |
| 50.0 hertz single component and 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Body Width:   |
| 1.625 inches  |
| Body Height:  |
| 1.625 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Current:  |
| 600.0 milliamperes ac single component single secondary   |
| Winding Operating Voltage:  |
| 6.30 ac volts single component single secondary   |
| Test Data Document:   |
| 36180-96-15613 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                               |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 5 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
|   |

## NSN 5950-00-114-1510

Power Transformer - Page 2 of 2

**Fiig:** A058b0

