

View Online at <https://aerobasegroup.com/nsn/5950-00-115-5425>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

Inductance Type:

Swinging

Inductance Rating:

40.00 millihenries single component single winding and 100.00 millihenries single component single winding

Body Length:

2.500 inches

Body Width:

2.312 inches

Body Height:

2.062 inches

End Application:

Wsd: austin ship class lpd-4 amphibious transport docks; avenger class mcm; arleigh burke class ddg; oliver perry class ffg; supply class aoe; spruance class dd (963)

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes dc single component single winding and 1.5 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.900 single component single winding

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0