

View Online at <https://aerobasegroup.com/nsn/5950-00-115-5425>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.687 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.437 inches single mounting facility single center group

**Inductance Type:**

Swinging

**Inductance Rating:**

40.00 millihenries single component single winding and 100.00 millihenries single component single winding

**Body Length:**

2.500 inches

**Body Width:**

2.312 inches

**Body Height:**

2.062 inches

**End Application:**

Wsd: austin ship class lpd-4 amphibious transport docks; avenger class mcm; arleigh burke class ddg; oliver perry class ffg; supply class aoe; spruance class dd (963)

**Winding Quantity:**

1 single component

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component single winding

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

500.0 milliamperes dc single component single winding and 1.5 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.900 single component single winding

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

2 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0