

View Online at <https://aerobasegroup.com/nsn/5950-00-117-3932>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

50.0 hertz and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.062 inches

Body Width:

2.562 inches

Body Height:

3.062 inches

End Application:

Yellowstone class ad-41; forrestal class cv; spruance class dd (963); nimitz class cvn; emory s. Land class as

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange and unthreaded hole single group

Winding Function And Quantity:

2 primary and 1 secondary single component

Winding Operating Current:

400.0 milliamperes ac single component single secondary

Winding Operating Voltage:

56.00 ac volts single component single secondary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0