## NSN 5950-00-123-5830

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-123-5830

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.440 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.120 inches single mounting facility single center group

#### **Overall Height:**

2.610 inches

#### **Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component

#### **Body Length:**

1.810 inches

#### **Body Width:**

1.500 inches

#### **Body Height:**

2.300 inches

## **Maximum Operating Temp:**

65.0 degrees celsius

#### **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

#### Thread Size:

0.138 inches single group

#### **Winding Operating Current:**

103.0 milliamperes ac single component single secondary

## **Winding Operating Voltage:**

82.00 ac volts single component single secondary

## **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

7 solder stud

# NSN 5950-00-123-5830

Power Transformer - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0