## NSN 5950-00-126-1564

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-126-1564

Not established  Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group  Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component  Body Length: 2.750 inches Body Width: 2.375 inches Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Winding Operating Current: 10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity: 11 turret  Shelf Life: N/a	
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.125 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.750 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.750 inches Body Width: 2.375 inches Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Reliability Indicator:
2.125 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  1.750 inches single mounting facility single center group  Frequency Rating:  400.0 hertz single component  Input-output Phase Relationship:  Single phase to single phase single component  Body Length:  2.750 inches  Body Width:  2.375 inches  Body Height:  3.812 inches  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded stud single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	
Center To Center Distance Between Mounting Facilities Parallel To Width:  1.750 inches single mounting facility single center group  Frequency Rating:  400.0 hertz single component Input-output Phase Relationship:  Single phase to single phase single component  Body Length:  2.750 inches  Body Width:  2.375 inches  Body Height:  3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity:  4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life: N/a	-
1.750 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.750 inches Body Width: 2.375 inches Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	2.125 inches single mounting facility single center group
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: 2.750 inches Body Width: 2.375 inches Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Width:
400.0 hertz single component  Input-output Phase Relationship: Single phase to single phase single component  Body Length: 2.750 inches  Body Width: 2.375 inches  Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Winding Operating Current: 10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity: 11 turret  Shelf Life: N/a	1.750 inches single mounting facility single center group
Input-output Phase Relationship: Single phase to single phase single component  Body Length: 2.750 inches  Body Width: 2.375 inches  Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Frequency Rating:
Single phase to single phase single component  Body Length: 2.750 inches  Body Width: 2.375 inches  Body Height: 3.812 inches  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity: 11 turret  Shelf Life: N/a	400.0 hertz single component
Body Length:  2.750 inches Body Width:  2.375 inches Body Height:  3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity:  4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:  1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi):  32 single group Thread Size:  0.138 inches single group Winding Operating Current:  10.0 milliamperes ac single component 1st secondary Winding Operating Voltage:  36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity:  11 turret Shelf Life: N/a	Input-output Phase Relationship:
2.750 inches Body Width: 2.375 inches Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Single phase to single phase single component
Body Width:  2.375 inches  Body Height:  3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity:  4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:  1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi):  32 single group Thread Size:  0.138 inches single group Winding Operating Current:  10.0 milliamperes ac single component 1st secondary Winding Operating Voltage:  36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity:  11 turret Shelf Life: N/a	Body Length:
2.375 inches  Body Height: 3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	2.750 inches
Body Height:  3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity:  4 single group Mounting Method: Threaded stud single group Winding Function And Quantity:  1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi):  32 single group Thread Size:  0.138 inches single group Winding Operating Current:  10.0 milliamperes ac single component 1st secondary Winding Operating Voltage:  36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity:  11 turret Shelf Life: N/a	Body Width:
3.812 inches Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	2.375 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Body Height:
Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity: 11 turret  Shelf Life: N/a	3.812 inches
Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Inclosure Type:
4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi): 32 single group  Thread Size: 0.138 inches single group  Winding Operating Current: 10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 36.00 ac volts single component 1st secondary  Thread Series Designator: Unc single group  Terminal Type And Quantity: 11 turret  Shelf Life: N/a	Fully enclosed
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Mounting Facility Quantity:
Threaded stud single group  Winding Function And Quantity:  1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	4 single group
Winding Function And Quantity:  1 primary single component and 3 secondary single component  Thready Qty Per Inch (tpi):  32 single group  Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	Mounting Method:
1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Threaded stud single group
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Winding Function And Quantity:
Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	1 primary single component and 3 secondary single component
Thread Size:  0.138 inches single group  Winding Operating Current:  10.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	Thready Qty Per Inch (tpi):
<ul> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>10.0 milliamperes ac single component 1st secondary</li> <li>Winding Operating Voltage:</li> <li>36.00 ac volts single component 1st secondary</li> <li>Thread Series Designator:</li> <li>Unc single group</li> <li>Terminal Type And Quantity:</li> <li>11 turret</li> <li>Shelf Life:</li> <li>N/a</li> </ul>	32 single group
Winding Operating Current:  10.0 milliamperes ac single component 1st secondary Winding Operating Voltage:  36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity:  11 turret Shelf Life: N/a	Thread Size:
10.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 36.00 ac volts single component 1st secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	0.138 inches single group
Winding Operating Voltage:  36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	Winding Operating Current:
36.00 ac volts single component 1st secondary  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	10.0 milliamperes ac single component 1st secondary
Thread Series Designator: Unc single group Terminal Type And Quantity: 11 turret Shelf Life: N/a	Winding Operating Voltage:
Unc single group  Terminal Type And Quantity:  11 turret  Shelf Life:  N/a	36.00 ac volts single component 1st secondary
Terminal Type And Quantity:  11 turret  Shelf Life: N/a	Thread Series Designator:
11 turret Shelf Life: N/a	Unc single group
Shelf Life: N/a	Terminal Type And Quantity:
N/a	11 turret
	Shelf Life:
Unit Of Measure	N/a
Ont of modoure.	Unit Of Measure:

No

Demilitarization:

## NSN 5950-00-126-1564

Power Transformer - Page 2 of 2



Fiig:

A058b0