

View Online at <https://aerobasegroup.com/nsn/5950-00-127-7043>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.750 inches

Body Width:

2.380 inches

Body Height:

1.750 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

750.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

5.00 dc volts single component 3rd secondary

Special Features:

1primary winding; 5secondary windings; secondary voltage and current have been rectified

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0