NSN 5950-00-132-6799

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-132-6799 |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Frequency Rating: |
| 800.0 hertz single component and 1.1 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and brought out to terminal single component |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 2.750 inches |
| Body Height: |
| 4.125 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 60.0 milliamperes ac single component 2nd secondary and 250.0 milliamperes ac single component 2nd secondary |
| Terminal Type And Quantity: |
| 11 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A058b0