NSN 5950-00-133-2930

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-133-2930

Reliability Indicator:
Not established
Overall Length:
1.547 inches
Mounting Hole Diameter:
0.953 inches single group
Frequency Rating:
40.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core and brought out to terminal single component
Body Length:
1.547 inches
Body Outside Diameter:
2.219 inches
Overall Diameter:
2.219 inches
Inclosure Type:
Open
Mounting Facility Quantity:
Mounting Facility Quantity: 1 single group
1 single group
1 single group Mounting Method:
1 single group Mounting Method: Unthreaded hole single group
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead Shelf Life:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead Shelf Life: N/a
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead Shelf Life: N/a
Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead Shelf Life: N/a Unit Of Measure:
1 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Winding Operating Current: 50.0 milliamperes ac single component 2nd secondary Winding Operating Voltage: 626.00 ac volts single component 2nd secondary Terminal Type And Quantity: 11 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: