## NSN 5950-00-133-8908

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-133-8908

Reliability Indicator:
Not established
Overall Length:
2.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.625 inches single mounting facility single center group
Overall Height:
1.937 inches
Overall Width:
1.500 inches
Mounting Hole Diameter:
0.120 inches single group
Frequency Rating:
60.0 hertz single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
2.375 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unther aded halo significances
Unthreaded hole single group
Winding Function And Quantity:
Winding Function And Quantity:
Winding Function And Quantity:  1 primary and 1 control single component
Winding Function And Quantity:  1 primary and 1 control single component Winding Operating Voltage:
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary  Special Features:
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary  Special Features:  Plastic inclosure material
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary  Special Features:  Plastic inclosure material  Terminal Type And Quantity:
Winding Function And Quantity:  1 primary and 1 control single component Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary Special Features: Plastic inclosure material Terminal Type And Quantity: 4 tab, solder lug
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary  Special Features:  Plastic inclosure material  Terminal Type And Quantity:  4 tab, solder lug  Shelf Life:
Winding Function And Quantity:  1 primary and 1 control single component Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary Special Features: Plastic inclosure material Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Winding Function And Quantity:  1 primary and 1 control single component Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary Special Features: Plastic inclosure material Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Winding Function And Quantity:  1 primary and 1 control single component  Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary  Special Features:  Plastic inclosure material  Terminal Type And Quantity:  4 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:
Winding Function And Quantity:  1 primary and 1 control single component Winding Operating Voltage:  110.00 ac volts and 400.00 ac volts single component single primary Special Features: Plastic inclosure material Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: