NSN 5950-00-134-5883

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-134-5883

	ibility Indicator:
	rdous Locations/environmental Protection:
	ture resistant and vibration resistant
	er To Center Distance Between Mounting Facilities Parallel To Length:
) inches single mounting facility single center group
	er To Center Distance Between Mounting Facilities Parallel To Width:
) inches single mounting facility single center group
-	uency Rating:
	negahertz single component and 5.0 megahertz single component
•	t-output Phase Relationship:
-	e phase to single phase single component
Body	/ Length:
	2 inches
Body	/ Width:
2.000) inches
Body	/ Height:
1.875	5 inches
Inclo	sure Type:
Fully	enclosed
Mou	nting Facility Quantity:
4 sin	gle group
Mou	nting Method:
Threa	aded hole single group
Winc	ling Function And Quantity:
1 prir	nary single component and 1 secondary single component
Thre	ad Size:
0.138	3 inches single group
Winc	ling Operating Current:
50.0	amperes dc single component single secondary
Winc	ling Operating Voltage:
6.00	ac kilovolts single component single primary
Thre	ad Series Designator:
Unc	single group
Term	inal Type And Quantity:
4 wir	e lead
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	

NSN 5950-00-134-5883

Power Transformer - Page 2 of 2

Fiig: A058b0

