

View Online at <https://aerobasegroup.com/nsn/5950-00-135-0788>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

Frequency Rating:

120.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 3.052 inches and 3.072 inches

Body Width:

Between 2.615 inches and 2.635 inches

Body Height:

Between 4.240 inches and 4.260 inches

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

700.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

385.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0