

View Online at <https://aerobasegroup.com/nsn/5950-00-135-9486>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 4.562 inches and 4.688 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.640 inches single mounting facility single center group and 3.734 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.953 inches single mounting facility single center group and 3.047 inches single mounting facility single center group

**Overall Height:**

Between 5.531 inches and 6.063 inches

**Overall Width:**

Between 3.875 inches and 4.000 inches

**Frequency Rating:**

45.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 7 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

3.0 amperes ac single component 3rd primary

**Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary

**Test Data Document:**

70117-580c23 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

20 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0