

View Online at <https://aerobasegroup.com/nsn/5950-00-136-5556>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.125 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.625 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

2.625 inches

**Body Width:**

2.125 inches

**Body Height:**

2.625 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

6.0 milliamperes dc single component 2nd secondary

**Winding Operating Voltage:**

107.50 ac volts single component single primary and 119.50 ac volts single component single primary

**Special Features:**

1 primary winding; 5 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

14 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0