

View Online at <https://aerobasegroup.com/nsn/5950-00-136-5556>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.625 inches

Body Width:

2.125 inches

Body Height:

2.625 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

6.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

107.50 ac volts single component single primary and 119.50 ac volts single component single primary

Special Features:

1 primary winding; 5 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

14 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0