

View Online at <https://aerobasegroup.com/nsn/5950-00-137-4068>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.050 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.900 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

5.5 watts single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

3.100 inches

**Body Width:**

2.870 inches

**Body Height:**

1.720 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

47.0 milliamperes ac single component single primary

**Winding Operating Voltage:**

60.40 ac volts single component 2nd secondary

**Special Features:**

1 primary winding; 6 secondary windings

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

26 pin and 1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0