

View Online at <https://aerobasegroup.com/nsn/5950-00-137-8865>

Reliability Indicator:

Not established

Overall Length:

Between 1.870 inches and 1.890 inches

Mounting Hole Diameter:

0.370 inches single group and 0.390 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Width:

Between 1.240 inches and 1.260 inches

Body Height:

Between 0.870 inches and 0.890 inches

Maximum Operating Temp:

170.0 degrees celsius

Distance Between Mounting Facility Centers:

1.557 inches single mounting facility single center group and 1.567 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

1.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

2.00 ac volts single component 1st secondary

Test Data Document:

92220-t050-025 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0