

View Online at <https://aerobasegroup.com/nsn/5950-00-138-0511>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

14.950 inches single mounting facility single center group and 15.050 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.950 inches single mounting facility single center group and 9.050 inches single mounting facility single center group

Overall Height:

10.690 inches

Overall Width:

Between 10.380 inches and 10.500 inches

Mounting Hole Diameter:

0.450 inches single group and 0.480 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

16.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

2.1 amperes ac single component all secondary

Winding Power Rating:

10.5 kilovolt-amperes single component all secondary

Winding Operating Voltage:

5.00 ac kilovolts single component all secondary

Special Features:

Coolant system; carrying handles 2

Test Data Document:

24930-160106 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0