

View Online at <https://aerobasegroup.com/nsn/5950-00-138-2782>

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.100

**Overall Height:**

0.375 inches

**Inductance Rating:**

700.00 microhenries single component single primary

**Frequency Rating:**

60.0 hertz single component

**Primary To Secondary Turn Ratio:**

1 to 1 to 1 single component

**Overall Diameter:**

0.610 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Dc Resistance Rating In Ohms:**

6.300 single component single primary

**Winding Operating Voltage:**

200.00 ac volts single component single primary

**Special Features:**

Scr trigger

**Test Data Document:**

95542-151-139 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A058b0