

View Online at <https://aerobasegroup.com/nsn/5950-00-139-9690>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Frequency Rating:

57.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded and brought out to terminal single component

Body Length:

1.250 inches

Body Outside Diameter:

2.250 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

4.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

3.50 ac volts single component 2nd secondary

Test Data Document:

92220-t053-102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0