

View Online at <https://aerobasegroup.com/nsn/5950-00-139-9700>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.802 inches single mounting facility single center group and 2.822 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group

**Frequency Rating:**

45.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

Between 3.370 inches and 3.390 inches

**Body Width:**

Between 2.800 inches and 2.820 inches

**Body Height:**

Between 2.990 inches and 3.010 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 4 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

8.5 amperes dc single component 2nd secondary

**Winding Operating Voltage:**

8.50 dc volts single component 2nd secondary

**Special Features:**

Secondarily windings 2, 3, 4, voltage and current have been rectified

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

15 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0