

View Online at <https://aerobasegroup.com/nsn/5950-00-139-9953>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.750 inches

Body Width:

3.625 inches

Body Height:

4.750 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

830.0 milliamperes ac single component single secondary

Winding Power Rating:

200.0 volts-amperes single component single secondary

Winding Operating Voltage:

190.00 ac volts single component single primary and 200.00 ac volts single component single primary and 210.00 ac volts single component single primary and 220.00 ac volts single component single primary and 230.00 ac volts single component single primary and 240.00 ac volts single component single primary

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0