

View Online at <https://aerobasegroup.com/nsn/5950-00-146-8186>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

6.250 inches

Body Width:

5.000 inches

Body Height:

4.750 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 11 secondary single component

Winding Operating Current:

600.0 milliamperes dc single component 2nd secondary

Winding Operating Voltage:

41.00 dc volts single component 4th secondary

Special Features:

1 primary winding; 11 secondary windings; secondary voltage and current rated as dc

Terminal Type And Quantity:

32 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0