

View Online at <https://aerobasegroup.com/nsn/5950-00-146-9395>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.906 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.813 inches single mounting facility single center group

Impedance Rating In Ohms:

100.0 single component single primary

Frequency Rating:

1.0 kilohertz single component and 11.0 kilohertz single component

Maximum Transformer Power Rating:

1.2 watts single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

1.438 inches

Body Width:

1.438 inches

Body Height:

1.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

240.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0