

View Online at <https://aerobasegroup.com/nsn/5950-00-147-0221>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.870 inches single mounting facility single center group and 5.880 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.995 inches single mounting facility single center group and 5.005 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.219 inches single group

**Frequency Rating:**

380.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

Between 6.484 inches and 6.510 inches

**Body Width:**

Between 5.995 inches and 6.005 inches

**Body Height:**

Between 4.483 inches and 4.515 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Operating Voltage:**

9.518 ac volts single component 1st secondary

**Test Data Document:**

92220-t050-034 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0