

View Online at <https://aerobasegroup.com/nsn/5950-00-147-0221>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.870 inches single mounting facility single center group and 5.880 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.995 inches single mounting facility single center group and 5.005 inches single mounting facility single center group

Mounting Hole Diameter:

0.219 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 6.484 inches and 6.510 inches

Body Width:

Between 5.995 inches and 6.005 inches

Body Height:

Between 4.483 inches and 4.515 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Voltage:

9.518 ac volts single component 1st secondary

Test Data Document:

92220-t050-034 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0