

View Online at <https://aerobasegroup.com/nsn/5950-00-147-7528>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.109 inches single mounting facility single center group and 2.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 2.625 inches and 2.750 inches

Body Width:

Between 2.250 inches and 2.375 inches

Body Height:

Between 2.687 inches and 2.812 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

100.0 milliamperes dc single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0