## NSN 5950-00-148-2766

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-148-2766

Reliability I	ndicator:
---------------	-----------

Not established

#### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.700 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.400 inches single mounting facility single center group

**Overall Height:** 

0.630 inches

#### Frequency Rating:

10.0 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

**Body Length:** 

0.880 inches

**Body Width:** 

0.630 inches

**Body Height:** 

0.480 inches

## Installation For Which Designed:

Indoor portable

## **Inclosure Type:**

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

### Thready Qty Per Inch (tpi):

56 single group

#### **Thread Size:**

0.086 inches single group

## **Winding Operating Current:**

70.0 milliamperes dc single component single primary

## **Winding Operating Voltage:**

15.00 ac volts single component single primary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

3 pin and 3 turret

## Shelf Life:

N/a

# **NSN 5950-00-148-2766**Current Transformer - Page 2 of 2



			ure:	

Demilitarization:

No

Fiig:

A058b0