NSN 5950-00-150-1023

Saturable Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-150-1023

Deliahilitu ludiastau.
Reliability Indicator:
Not established
Overall Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.375 inches single mounting facility single center group
Overall Height:
3.250 inches
Overall Width:
3.130 inches
Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
400.0 hertz single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
1.250 inches
Body Width:
2.000 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
2 primary single component and 1 secondary single component and 1 control single component
Saturation Current Rating:
500.0 milliamperes
Dc Resistance Rating In Ohms:
5.300 single component all primary
Winding Operating Voltage:
115.00 ac volts single component all primary
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

_.

NSN 5950-00-150-1023

Saturable Reactor - Page 2 of 2



em			

No

Fiig:

A058b0