

View Online at <https://aerobasegroup.com/nsn/5950-00-151-7431>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 1.76 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.594 inches

Body Width:

2.094 inches

Body Height:

2.312 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Special Features:

Shield w/solder lug type terminal, primary winding w/115 v rating, secondary windings rated 6.3 v at 1.2 amp, 6.3 v at 2.22 amp, 6.3 v at 2.5 amp, 7.5 v at 480 ma, and 600 v at 300 ua

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0