

View Online at <https://aerobasegroup.com/nsn/5950-00-152-8059>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility single center group

Mounting Hole Diameter:

0.166 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.250 inches

Body Width:

1.500 inches

Body Height:

2.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.2 amperes dc single component single secondary

Winding Operating Voltage:

86.00 ac volts single component single primary and 88.00 ac volts single component single primary and 90.00 ac volts single component single primary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0