

View Online at <https://aerobasegroup.com/nsn/5950-00-153-4555>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.063 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.156 inches single mounting facility single center group

Frequency Rating:

5.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.620 inches

Body Width:

2.680 inches

Body Height:

2.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

250.0 milliamperes dc single component single secondary

Winding Operating Voltage:

890.00 ac volts single component single secondary and 920.00 ac volts single component single secondary and 940.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0