NSN 5950-00-154-0158

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-154-0158

| R | e۱ | lia | h | ili | it۱ | <i>,</i> I | n | d | i | са | t | n | r | |
|---|----|-----|---|-----|-----|------------|---|---|---|----|---|---|---|--|
| | CI | IIa | v | ш | | , , | | u | ľ | va | u | v | | |

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.172 inches single mounting facility single center group and 1.204 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 1.563 inches and 1.625 inches

Body Width:

Between 1.563 inches and 1.625 inches

Body Height:

Between 2.250 inches and 2.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Voltage:

8.25 ac volts single component all secondary and 12.00 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0