

View Online at <https://aerobasegroup.com/nsn/5950-00-155-4730>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.740 inches single mounting facility single center group and 2.760 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.115 inches single mounting facility single center group and 1.135 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Length:

Between 3.240 inches and 3.260 inches

Body Width:

Between 3.427 inches and 3.447 inches

Body Height:

Between 1.615 inches and 1.635 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

100.0 milliamperes ac single component all secondary

Winding Operating Voltage:

7.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0