# NSN 5950-00-155-4730

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-155-4730

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.740 inches single mounting facility single center group and 2.760 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.115 inches single mounting facility single center group and 1.135 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to terminal single component

#### **Body Length:**

Between 3.240 inches and 3.260 inches

#### **Body Width:**

Between 3.427 inches and 3.447 inches

#### **Body Height:**

Between 1.615 inches and 1.635 inches

#### **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

# Thread Size:

0.138 inches single group

#### **Winding Operating Current:**

100.0 milliamperes ac single component all secondary

# **Winding Operating Voltage:**

7.00 ac volts single component single primary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

21 turret

#### Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5950-00-155-4730

Power Transformer - Page 2 of 2



Fiig:

A058b0